
BO34M-01

# **REMOVAL**

#### 1. REMOVE WIPER ARMS

Remove the wiper arm head cap, 2 nuts and 2 wiper arms.



#### 2. REMOVE COWL TOP VENTILATOR LOUVER


- (a) Remove the 5 screws and 6 clips.
- (b) Using a screwdriver, remove the cowl top ventilator louver.

HINT:

Tape the screwdriver tip before use.

#### 3. REMOVE REMOVABLE ROOF HOOK

Remove the 2 screws and removable roof hook.



#### 4. REMOVE FRONT PILLAR GARNISHS


(a) Using a screwdriver, remove the front pillar garnish. HINT:

Tape the screwdriver tip before use.

(b) Employ the same manner described above to the other side.

#### 5. REMOVE SUN VISORS

Remove the 4 screws and sun visors.




### 6. REMOVE MAP LIGHT ASSEMBLY

(a) Using a screwdriver, remove the map light cover. HINT:

Tape the screwdriver tip before use.

(b) Remove the 2 screws and map light assembly, then disconnect the connector.



7. REMOVE FRONT ROOF HEADLINING TRIM


Using a screwdriver, remove the front roof headlining. HINT:

Tape the screwdriver tip before use.

8. REMOVE INNER REAR VIEW MIRROR ASSEMBLY

2000 MR2 (RM760U)

Author: Date: 1231




### 9. REMOVE WINDSHIELD OUTSIDE MOULDING

(a) Using a knife, cut off the moulding as shown in the illustration

#### NOTICE:

Do not damage the body with the knife.

(b) Remove the remaining moulding.




#### 10. REMOVE WINDSHIELD GLASS

- (a) Insert a piano wire between the body and glass, let it pass through.
- (b) Tie both wire ends to wooden blocks or similar objects.

### **NOTICE:**

Be careful not to damage the wire harness.



(c) Cut the adhesive by pulling the piano wire around it.

#### NOTICE:

When separating the glass, take care not to damage the paint and exterior ornaments. To prevent the safety pad from being scratched when removing the windshield, place a plastic sheet between the piano wire and safety pad.

## HINT:

Apply protective tape to the outer surface to keep the surface from being scratched.

(d) Remove the glass.

### **NOTICE:**

Leave the adhesive on the body as much as possible when cutting off the glass.

2000 MR2 (RM760U)

Author: Date: 1232