DI09C-08

DTC	P0101	Mass Air Flow Circuit Range/Performance Problem

CIRCUIT DESCRIPTION

Refer to DTC P0100 on page DI-23.

DTC No.	DTC Detection Condition	Trouble Area	
P0101	Conditions (a) and (b) continue 10 sec. or more with engine speed 900 rpm or less: (2 trip detection logic) (a) Throttle valve fully closed (b) Mass air flow meter output > 2.2 V		
	Conditions (a) and (b) continue 10 sec. or more with engine speed 1,500 rpm or more: (2 trip detection logic) (a) VTA ≥ 0.63 V (b) Mass air flow meter output < 1.06 V	Mass air flow meter	

INSPECTION PROCEDURE

HINT:

Read freeze frame data using TOYOTA hand—held tester or OBD II scan tool. Because freeze frame records the engine conditions when the malfunction is detected. When troubleshooting, it is useful for determining whether the vehicle was running or stopped, the engine was warmed up or not, the air—fuel ratio was lean or rich, etc. at the time of the malfunction.

1 Are there any other codes (besides DTC P0101) being output?

NO

Replace mass air flow meter.

YES

Go to relevant DTC chart (See page DI-14).

2000 MR2 (RM760U)

Author: Date: 191