



BODY INSPECTION

MA03R-0

1. TIGHTEN BOLTS AND NUTS ON CHASSIS AND BODY Tighten these parts:

Seat-to-body mounting bolts

Torque: 37 N-m (375 kgf-cm, 27 ft-lbf)

• Rear suspension member–to–body mounting bolts Torque: 80 N-m (816 kgf-cm, 59 ft-lbf)

2. BODY INSPECTION

- (a) Check the body exterior for dents, scratches and rust.
- (b) Check the underbody for rust and damage. If necessary, replace or repair.

3. ROAD TEST

B10852

- (a) Check the engine and chassis for abnormal noises.
- (b) Check that the vehicle does not wander or pull to one side
- (c) Check that the brakes work properly and do not drag.
- (d) Do setting of the parking brake shoes and drum.

4. FINAL INSPECTION

- (a) Check the operation of the body parts:
 - Front hood
 Auxiliary catch operates properly
 Hood locks securely when closed
 - Doors
 Door locks operate properly
 Doors close properly
 - Engine hood
 Door lock operates properly
 - Seat adjusts easily and locks securely in any position

Seat back locks securely in any position

(b) Be sure to deliver a clean car.

Especially check:

- Steering wheel
- Shift lever knob
- All switch knobs
- Seats