

**TORQUE SPECIFICATION**

Parttightened	N·m	kgf·cm	ft·lbf
<b>FRONT AXLE</b>			
Hub nut	103	1,050	76
Tie rod end lock nut	47	479	35
Steering knuckle x Shock absorber	140	1,430	103
Brake caliper x Steering knuckle	109	1,112	80
Axle hub x Steering knuckle	56	571	41
Steering knuckle x Tie rod end	49	500	36
Lower suspension arm x Steering knuckle	98	1,000	72
<b>FRONT SUSPENSION</b>			
Suspension support x Body	39	400	29
Shock absorber center nut	51	520	38
Flexible hose x Shock absorber	29	296	21
ABS speed sensor wire harness x Shock absorber	8.0	82	71 in.·lbf
Lower suspension arm, suspension member brace x Body	73	745	54
Lower suspension arm x Suspension member	87	887	64
Suspension member brace x Body	75	765	55
Stabilizer bar bracket x Body	30	306	22
Stabilizer bar link x Stabilizer bar	44	449	32
Stabilizer bar link x Lower suspension arm	18	184	13
<b>REAR AXLE</b>			
Hub nut	103	1,050	76
Axle carrier x Shock absorber	173	1,765	128
Brake caliper x Axle carrier	59	602	34
Axle hub x Drive shaft	216	2,200	159
ABS speed sensor x Axle carrier	8.0	82	71 in.·lbf
ABS speed sensor wire harness clamp x Axle carrier	5.0	51	44 in.·lbf
Strut rod x Axle carrier	78	796	58
No. 1 lower suspension arm x Axle carrier	103	1,051	76
No. 2 lower suspension arm x Axle carrier	49	500	36
Dust cover x Axle carrier	8.3	85	74 in.·lbf
<b>REAR DRIVE SHAFT</b>			
Drive shaft center bearing case lock bolt	64	650	47
<b>REAR SUSPENSION</b>			
Flexible hose x Shock absorber	29	296	21
Suspension support x Body	80	816	59
Shock absorber center nut	73	745	54
Strut rod x Suspension member	78	796	58
No. 1 lower suspension arm x Suspension member	87	887	64
No. 2 lower suspension arm x Suspension member	87	887	64
Stabilizer bar bracket set bolt	39	398	29
Stabilizer bar link set nut	44	449	32